



high temperature Ni-CD battery



Product Description :

List Of Ni-CD High Temperature Cells

Type	Model	Diemeter (mm)	Height (mm)	Capacity (mAh)	Operating Temperature (°C)
AAA	LA-AAA30T	10.5 +0 -0.7	43.0 ±0.5	300	-20 to 70
AA	LA-AA80T	14.5 +0 -0.7	50.0±0.5	800	-20 to 70
	LA-AA90T	14.5 +0 -0.7	50.0±0.5	900	-20 to 70
A	LA-4/5A110T	17.0 +0 -0.7	42.5±0.5	1100	-20 to 70
	LA-A130T	17.0 +0 -0.7	49.5±0.5	1300	-20 to 70
SC	LA-4/5SC120T	23.0 +0 -1.0	33.5±0.5	1200	-20 to 70
	LA-SC130T	23.0 +0 -1.0	42.5±0.5	1300	-20 to 70
	LA-SC140T	23.0 +0 -1.0	42.5±0.5	1400	-20 to 70

	LA-SC150T	23.0 +0 -1.0	42.5±0.5	1500	-20 to 70
	LA-SC160T	23.0 +0 -1.0	42.5±0.5	1600	-20 to 70
	LA-SC170T	23.0 +0 -1.0	42.5±0.6	1700	-20 to 70
	LA-SC180T	23.0 +0 -1.0	42.5±0.5	1800	-20 to 70
	LA-SC190T	23.0 +0 -1.0	42.5±0.5	1900	-20 to 70
	LA-SC200T	23.0 +0 -1.0	42.5±0.5	2000	-20 to 70
C	LA-C220T	25.8 +0 -1.0	49.5±0.5	2200	-20 to 70
	LA-C250T	25.8 +0 -1.0	49.5±0.5	2500	-20 to 70
	LA-C280T	25.8 +0 -1.0	49.5±0.5	2800	-20 to 70
	LA-C300T	25.8 +0 -1.0	49.5±0.5	3000	-20 to 70
D	LA-D400T	33.0 +0 -1.0	60.0+0 -1.5	4000	-20 to 70
	LA-D450T	33.0 +0 -1.0	60.0+0 -1.5	4500	-20 to 70
	LA-D500T	33.0 +0 -1.0	60.0+0 -1.5	5000	-20 to 70
	LA-1/2D220T	33.0 +0 -1.0	36.0 +0 -1.5	2200	-20 to 70