



high temperature Ni-MH battery



Product Description :

List Of Ni-MH High Temperature Cells					
Type	Model	Diemeter (mm)	Height (mm)	Capacity (mAh)	Operating Temperature (°C)
AAA	LA-AAA30HT	10.5 +0 -0.7	43.0 ±0.5	300	-20 to 70
	LA-AAA40HT	10.5 +0 -0.7	43.0 ±0.5	400	-20 to 70
	LA-AAA50HT	10.5 +0 -0.7	43.0 ±0.5	500	-20 to 70
	LA-AAA60HT	10.5 +0 -0.7	43.0 ±0.5	600	-20 to 70
AA	LA-AA60HT	14.5 +0 -0.7	50.0±0.5	600	-20 to 70
	LA-AA70HT	14.5 +0 -0.7	50.0±0.5	700	-20 to 70
	LA-AA80HT	14.5 +0 -0.7	50.0±0.5	800	-20 to 70
	LA-AA85HT	14.5 +0 -0.7	50.0±0.5	850	-20 to 70
	LA-AA90HT	14.5 +0 -0.7	50.0±0.5	900	-20 to 70

A	LA-AA100HT	14.5 +0 -0.7	50.0±0.5	1000	-20 to 70	
	LA-AA110HT	14.5 +0 -0.7	50.0±0.5	1100	-20 to 70	
	LA-AA120HT	14.5 +0 -0.7	50.0±0.5	1200	-20 to 70	
	LA-AA130HT	14.5 +0 -0.7	50.0±0.5	1300	-20 to 70	
	LA-AA140HT	14.5 +0 -0.7	50.0±0.5	1400	-20 to 70	
	LA-AA150HT	14.5 +0 -0.7	50.0±0.5	1500	-20 to 70	
	LA-AA160HT	14.5 +0 -0.7	50.0±0.5	1600	-20 to 70	
	LA-A180HT	17.0 +0 -0.7	49.5±0.5	1800	-20 to 70	
	LA-A190HT	17.0 +0 -0.7	49.5±0.5	1900	-20 to 70	
	LA-A200HT	17.0 +0 -0.7	49.5±0.5	2000	-20 to 70	
	LA-A210HT	17.0 +0 -0.7	49.5±0.5	2100	-20 to 70	
	LA-4/3A250HT	17.0 +0 -0.7	66.5±0.5	2500	-20 to 70	
	LA-4/3A260HT	17.0 +0 -0.7	66.5±0.5	2600	-20 to 70	
	LA-4/3A270HT	17.0 +0 -0.7	66.5±0.5	2700	-20 to 70	
	LA-4/3A280HT	17.0 +0 -0.7	66.5±0.5	2800	-20 to 70	
	LA-4/3A290HT	17.0 +0 -0.7	66.5±0.5	2900	-20 to 70	
	LA-4/3A300HT	17.0 +0 -0.7	66.5±0.5	3000	-20 to 70	
	SC	LA-SC130HT	23.0 +0 -1.0	42.5±0.5	1300	-20 to 70
		LA-SC140HT	23.0 +0 -1.0	42.5±0.5	1400	-20 to 70
		LA-SC150HT	23.0 +0 -1.0	42.5±0.5	1500	-20 to 70
LA-SC160HT		23.0 +0 -1.0	42.5±0.5	1600	-20 to 70	
LA-SC170HT		23.0 +0 -1.0	42.5±0.6	1700	-20 to 70	
LA-SC180HT		23.0 +0 -1.0	42.5±0.5	1800	-20 to 70	
LA-SC190HT		23.0 +0 -1.0	42.5±0.5	1900	-20 to 70	
LA-SC200HT		23.0 +0 -1.0	42.5±0.5	2000	-20 to 70	
LA-SC210HT		23.0 +0 -1.0	42.5±0.5	2100	-20 to 70	
LA-SC220HT		23.0 +0 -1.0	42.5±0.5	2200	-20 to 70	
LA-SC230HT		23.0 +0 -1.0	42.5±0.5	2300	-20 to 70	
LA-SC240HT		23.0 +0 -1.0	42.5±0.5	2400	-20 to 70	
LA-SC250HT		23.0 +0 -1.0	42.5±0.5	2500	-20 to 70	