



Via L.da Vinci, 47 -20030 Senago (MI)
Tel.029989684 info@larsonnuova.it
www.larsonnuova.com

SPECIFICATION FOR APPROVAL

CUSTOMER/客户 : 01061
ARTICLE/品名: SWITCHING MODE POWER SUPPLY
SPECIFICATION /规格: UL/GS/CE/SAA Desktop/桌面式
MODEL NO/产品型号.: 836-240150W
OUR PART NO./产品编号: -240150-19916D
CUSTOMER P. N/客户料号:
INPUT/输入 : 100-240V AC 50/60Hz
OUTPUT/输出: 24.0V DC 1.5A
INPUT/输入 : 100-240V AC 50/60Hz

1.Compendium/简述

The document details the electrical, mechanical and environmental specifications of a SMPS, the power supply provides 36 W continuous output power.
资料详细描述了一款 36 W(连续输出功率)开关电源的电气性，结构性及环境等要求。
The power supply shall meet the RoHS requirements.
此款电源符合 RoHS 要求。

1.1 Description/描述

- ☐ SMPS Adapter(Wall mount)/插墙式适配器
- ☒ SMPS Adapter(Desk-top)/桌面型适配器
- ☐ SMPS Unit (With Case)/带铁壳型
- ☐ SMPS Adapter(Interchangeable)/可换头适配器
- ☐ Open Frame/开放式结构
- ☐ Others/其他

2. Input Characteristics/输入特性

2.1 Input Voltage & Frequency/输入电压与频率

The range of input voltage is from 90Vac to 264Vac with a single phase.
输入电压范围：从 90Vac 到 264Vac，单相输入。

	Minimum/最小	Nominal/额定值	Maximum/最大
Input Voltage/输入电压	90Vac	100Vac~240Vac	264Vac
Input Frequency/输入频率	47Hz	60Hz/50Hz	63Hz

2.2 Input AC Current/AC 输入电流

1.0A max @ 100-240Vac input & Full load/在 100 – 240 Vac 输入和满载条件下最大 1.0A 有效值

2.3 Inrush Current (cold start)/浪涌电流(冷启动)

The inrush current will not exceed 60A at 100-240Vac input and Max load for a cold start at 25℃

在 100-240V 交流电输入和最大负载冷启动环境 25℃时浪涌电流不能超过 60A

2.4 Average Efficiency/平均效率

While input 115Vac and 230Vac, the average efficiency is more than 87.40%.

The test point is at 25%, 50%, 75% and 100% of max load respectively.

在输入 115Vac 和 230Vac 条件下，平均效率不小于 87.40%。

测试点分别是最大载的 25%,50%,75%和 100%。

2.5 Energy Consumption /空载功耗

While input 115Vac or 230Vac and the output is no load,the input power loss must be less than 0.1W

在输入 115Vac/230Vac 时,空载功耗小于 0. 1W

3. Output Characteristics/输出特性

3.1 Static Output Characteristics <Vo & R+N>/静态输出特性<输出纹波+噪音>

Output	Rated Load/额定负载			Output Range	R+N	Remark
Rate	Min. Load	Max. Load		输出电压范围	纹波与噪声	备注
+24V	0.0A	1.5A		22.8V-25.2V	200mVp-p	

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 10uF electrolysis capacitor.

(test under the condition of rated input and rated output)

纹波与噪声：量测时示波器选用 **20MHz** 带宽限制,输出端要并联一颗 **0.1uF** 的陶瓷电容和一颗 **10uF** 的电解电容。(在额定输入及输出的条件下检测)

3.2 Line/ Load Regulation/线性/负载调整率

Output	Load Condition/负载条件		Line Regulation	Load Regulation	Remark
Rate	Min. Load	Max. Load	线性调整率	负载调整率	备注
+24V	0.0A	1.5A	± 3%	± 5%	

3.3 Turn - on Delay Time/开机延迟时间

3S max. @ 100 Vac to 240 Vac input & Full load

在 **100Vac** 到 **240Vac** 输入和满载条件下最大 **3S**

3.4 Hold-up Time/关机维持时间

5mS min. @ Full load & 100Vac/60Hz input turn off at worst case

在 **100Vac** 输入,满载同时最差情况下关机, 最小 **5mS**

3.5 Capacitance Load/容性负载

While input 100~240Vac and capacitance load is 470uF, the adapter can turn on normally and the output is in the rated range.

在输入 **100~240Vac**, **470uF** 容性负载条件下, 适配器能正常开机。

并且输出电压范围在额定范围下。

3.6 Output Overshoot / Undershoot/输出过冲/欠冲

10% max. When the power on or off

当电源开/关机时, 10%最大

3.7 Output Load Transient Response/输出负载瞬态响应

the output shall not exceed 10% of the nominal output voltage, load fluctuation: from 20% to 80%, R/S: 0.5A/uS, frequency: 100Hz duration and 8mS at 80%.

输出电压不能超过额定电压的 **10%**,负载变化: 从 **20%**到 **80%**, 斜率: **0.5A/uS**, 频率: **100Hz**, **80%**负载持续时间为 **8mS**.

4. Protection Requirements/保护要求

4.1 Over Current Protection/过流保护

Over Current Point Limited/过流点限制: $I > 1.95A$

The output shall hiccup when the over currents applied to the output rail, and shall be self-recovery when the fault condition is removed

当过电流时, 输出将进入打嗝模式, 当过流情况解除后, 产品将会自动恢复正常

4.2 Short Circuit Protection/短路保护

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be self-recovery when the fault condition is removed

当输出短路时, 产品输入功率降低且不会损伤, 当短路情况解除后, 产品将会自动恢复正常

4.3 Over Voltage Protection/过压保护

The power supply shall protection when the output over voltage。

当输出发生过压时, 产品进入保护模式。

5. Environment Requirements/环境要求

5.1 Operating Temperature and Relative Humidity/操作温/湿度要求

0°C to +40°C

10%RH to 90%RH

5.2 Storage Temperature and Relative Humidity/存储温/湿度要求

-20°C to +80°C

5%RH to 95%RH non-condensing @ Sea level shall be low 10,000 feet/低于 10,000 英尺

5.3 Vibration/振动

10 to 300Hz sweep at a constant acceleration of 1.0G(Breadth: 3.5mm) for 1Hour for each of the perpendicular axes X, Y, Z

扫描频率: 10 to 300Hz, 加速度: 1.0G(位移: 3.5mm), X, Y, Z 三垂直坐标轴向各振动 1 小时

6. Reliability Requirements/可靠性要求

6.1 Burn-in/煲机

The power supply shall be burn-in at least 4 Hours under normal input and
80% rated load at 40°C ± 5°C

产品至少要在 40°C ± 5°C 的环境及 80% 以上额定负载条件下煲机 4 小时

6.2 MTBF Qualification/平均间隔故障时间估算

The MTBF shall be at least 50,000hours at 25°C, Full load and nominal
input condition

平均间隔故障时间: 至少 50,000 小时, 25°C 环境及额定输入与满载条件下

7. EMI/EMS Standards/EMI/EMS 标准

7.1 EMI Standards/EMI 标准

- ☒ FCC Part15 class B ☐ EN55014-1 ☐ EN61204-3 (CISPR 22)
- ☒ EN55032 ☐ AS/NZS CISPR22 ☐ AS/NZS CISPR13 ☐ AS/NZS CISPR14. 1
- ☐ GB9254 ☐ GB13837 ☐ GB17625. 1
- ☐ J55022 ☐ J55013 ☐ J55014-1
- ☐ KN22 ☐ KN13 ☐ KN14-1
- ☐ CNS13438

7.2 EMS Standards/EMS 标准

- ☒ EN55035 ☐ EN55020 ☐ EN55014-2 ☐ EN61204-3

7.2.1 IEC 61000-4-2, electrostatic discharge(ESD) requirement/静电抗扰度要求

Discharge characteristic/静电规格	Test level/测试条件	Test criteria/测试标准
Air discharge/空气放电	+/-8KV	B
Contact discharge/接触放电	+/-4 KV	B

7.2.2 IEC 61000-4-4, electric fast transients(EFT) immunity requirement/电快速瞬变脉冲群

Coupling/测试端口	Test level/测试条件	Test criteria/测试标准
AC-input/交流输入	0.5KV	A
AC-input/交流输入	1KV	B

7.2.3 IEC 61000-4-5, surge capability requirement/浪涌抗扰度要求

Surge voltage/雷击电压	Test criteria/测试标准
Differential mode/差模 +/-2KV	A
Common mode/共模 +/-2KV	

7.2.4 Assessment criteria /评估标准

Acceptable criteria 可接受标准	Performance 性能
A	Performance is not allowed to be changed, any changes should be within the specified limits 性能不允许变化；如果性能会发生变化，则变化的范围在产品规格书规定的范围内。
B	During the testing process, the performance degradation is allowed within the specifications of the product specification. After the elimination, the equipment can return to normal and no reset or any manual intervention is allowed. . 设备在测试过程中，性能降低允许在产品规格书要求范围内，干扰消除后，设备能恢复正常，不允许出现复位和任何方式的人工干预。

8. Safety Standards/安规标准

8.1 Safety Accord with/安全:符合标准

- ☐ UL60950-1, CSA C22.2 NO. 60950-1 ☒ UL62368-1, CSA C22.2 NO. 62368-1
☐ UL1310
☐ IEC60950-1 ☒ IEC62368-1 ☐ IEC61558-1, IEC61558-2-16
☐ EN60950-1 ☒ EN62368-1 ☐ EN61558-1, EN61558-2-16
☐ AS/NZS 60950.1 ☒ AS/NZS 62368.1 ☐ AS/NZS 61558.1, AS/NZS 61558.2.16
☐ GB4943.1 ☐ GB8898
☐ J60950-1 ☐ J62368-1 ☐ J61558-1, J61558-2-16
☐ K60950-1 ☐ K60065
☐ CNS14336-1 ☐ CNS14408

Note: AC pins corresponding to relative national standards.

注：相应的 AC 插脚对应相应国家的标准。

8.2 Dielectric Strength(Hi-pot)/介电耐压强度(高压)

Primary to Secondary: 4242VDC / 5mA_{Max} / 60second(3 seconds for mass production)

初级对次级: 4242VDC / 5mA_{Max} / 60 秒(生产时高压测试时间: 3 秒)


8.3 Leakage Current/漏电流

0.25mA_{max}. at 264Vac / 50Hz / 在 264Vac / 50Hz 输入时，最大漏电流 0.25mA


8.4 Insulation Resistance/绝缘阻抗

50MΩ min. at primary to secondary add 500Vdc test voltage

在初级与次级间加 500Vdc 进行测试,最小绝缘阻抗 50MΩ




10. AC Cord Drawing/AC 线示意图:



11. DC Cord Drawing/DC 线示意图:

半成品线材:



线材规格:

- 1, UL2464 20AWG OD3.5±0.1 外被黑色. (印字)
- 2, 芯线颜色: 红线黑线 or 白线黑线.

芯线	红线黑线	红线接正极 黑线接负极.
颜色	白线黑线	白线接正极 黑线接负极.


拉力试验:

5Kg SR不脱落. DC线本体至少承受10Kg的拉力.

摇摆试验:


荷重200g 120° 角, 45回/分钟3000次Min.

成品线材:



注意事项:


- 1, DC PLUG: $\varnothing 2.1 \times \varnothing 5.5 \times 12.0$ 叉沟(黑胶芯).
- 2, SR SIZE: $6.6 \times 6.6 \times 2.4$
- 3, ★符号为重要参数项



设计	校对	批准	尺寸公差	
梁 颖	梁 成	高 峰	±0.05	±0.10
设计日期	材料	PVC	±0.15	±0.20
			±0.25	±0.30

12. Marking Drawing/铭牌示意图:

12. Marking Drawing/铭牌示意图:



名称: 镭雕				REV: A			
图号: 836-LB19916D				型号: 836-240150W		页号: 6 图寸: A4	
尺寸公差		比例		1:1 绘图		校对 批准	
±0.05	±0.10	单位	MM	刘惠娴	宋耀	吴国铭	
±0.15	±0.20	日期					

13. Package Drawing/包装示意图:

PLASTIC BAG/PE袋




WHITE BOX/白盒



CARDBOARD/纸板



PAPER CASE/纸箱



MECHANICAL DIMENSION:

	L(mm)	W(mm)	H(mm)
PLASTIC BAG	210	130	
WHITE BOX	143	70	60
CARDBOARD	370	296	
PAPER CASE	380	306	275

PACKING METHOD:

PACKING METHOD	10PCS/LAYER *4LAYERS
QTY	40PCS
N.W	7.0Kg
G.W	9.0Kg